

IN THE CLAIMS

Please amend claims 65 and 66 by rewriting the same as follows:

Sub B1
✓ 65. (Amended) A method of recording data on an optical disk having a diameter less than 140 mm and a recording area divided into a lead-in area, a program area and a lead-out area, said method comprising the steps of: providing user information for recording in a plurality of sectors in user track regions; providing control information for recording in a plurality of sectors in at least one control information region[, said control information including addresses of respective start sectors, each identifying a start sector of a respective user track]; encoding both said user information and said control information in a long distance error correction code having at least eight parity symbols; modulating the encoded user and control information; recording the modulated, encoded control information in said at least one control information region in either said lead-in area or said program area; and recording the modulated, encoded user information in said user track regions in said program area with a track pitch in the range between 0.646 μm and 1.05 μm . ✓

✓ 66. (Amended) Apparatus for recording data on an optical disk having a diameter less than 140 mm and a recording area divided into a lead-in area, a program area and a lead-out area, said apparatus comprising: input means for providing user information for recording in a plurality of sectors in user track regions and control information for recording in a plurality of sectors in at least one control information region[, said control information including addresses of respective start sectors, each identifying a start sector of a respective user track]; encoding means for encoding both said user information and said control information in a long distance error correction code having at least eight parity symbols; modular means for modulating the encoded user and control information; and recording means for recording the